

**BRAIDED OUTER CONDUCTOR****MODEL 213RT5****FEATURES**

Polar Electronic Industries Pty Ltd can supply your needs for coaxial cables made with a braided outer conductor, including some low-loss types. Coaxial cables may be supplied fitted with connectors to order, and cables mounting hardware is available.

CONSTRUCTION

The datasheet refers to common braided outer conductor cables, with the specifications showing the attenuation losses in dB per 100 metres of coaxial cable when used at various frequencies, and also the highest average power level for the coaxial cable at those frequencies.

NOTES

If you have other requirements please consult Polar, we have a wide range available including cables with a variety of impedances other than 50 ohms.

Abbreviations, Inner conductor:

- CB - copper braid
- CW - solid copper wire
- CS - copper strands
- DSCB - double silvered copper braid
- SCW - silvered copper wire
- SCS - silvered copper strands
- TCB - tinned copper braid
- TCBAF - tinned copper braid with aluminium foil
- TCS - tinned copper strands

MODEL NO	213RT5
IMPEDANCE	50 ohms
ATTENUATION	2.5 dB @ 40 MHz
ATTENUATION	3.5 dB @ 75 MHz
ATTENUATION	5.1 dB @ 160 MHz
ATTENUATION	9.0 dB @ 450 MHz
ATTENUATION	12.9 dB @ 900 MHz
POWER	2000 Watts @ 40 MHz
POWER	1500 Watts @ 75 MHz
POWER	1000 Watts @ 160 MHz
POWER	630 Watts @ 450 MHz
POWER	430 Watts @ 900 MHz
DIAMETER ϕ	10.1 mm (outer)
WEIGHT	13.3 kg/100m
INNER CONDUCTOR	SCW
OUTER CONDUCTOR	TCBAF
DIELECTRIC TYPE	Foam PE
OUTER SHEATH	PE
VELOCITY FACTOR	82 %
CAPACITANCE	65 pF

**POLAR ELECTRONIC INDUSTRIES PTY LTD**

COMMUNICATIONS ENGINEERS

ACN : 005 545 291 ABN : 74 711 768 638

9 - 15 FRIARS RD MOORABBIN 3189 VICTORIA AUSTRALIA

T : + 61 3 9555 2500 F : + 61 3 9555 1515 TF : 1800 33 5633 (Australia only)

E : polar@polarelec.com.au W : http://www.polarelec.com.au

